

MPSI CONNEX IEC INLET CONNECTORS, 702 Series:

Order Code 702-0004 – Fused/Switched IEC C14 Chassis Mount Inlet Conn, 15A, 250V, UL94V-0

| T +44 (0) 1256 817933 | www.mpsiconnex.com | sales@mpsiconnex.com |



Images are for Illustrative Purposes Only

3-Pole Chassis Mount Inlet IEC C14 Connector,
Fused, with I/O DPST Switch.

Separate Termination for Inlet Connector and Switch.

Faston Terminals 4.8mm x 0.8mm.

Panel Cut-Out 28.4mm x 48.4mm.

Rated at 10A / 250V with VDE, CCC & ENEC
& 15A / 250V with UL & cUL.

> TECHNICAL SPECIFICATION

VOLTAGE RATING:	250 V
CURRENT RATING:	10A (VDE, CCC & ENEC) 15A (UL & cUL)
INSULATION RESISTANCE:	OVER 100MΩ OVER 500V DC
DIELECTRIC W/STAND VOLT. BETWEEN TERMS:	2500V AC (50-60Hz) 1 MINUTE
DIELECTRIC W/STAND VOLT. TERMS TO BASE:	3750V AC (50-60Hz) 1 MINUTE
LEAKAGE CURRENT:	1mA
BODY MATERIAL:	BLACK GLASS FIBRE THERMOPLASTIC UL94V-0
ROHS COMPLIANT:	YES
PANEL CUT-OUT:	28.4mm x 48.4mm
FIXING CENTRES:	40mm
INSERTION & EXTRACTION FORCE:	1.35-7.0kgf
TERMINAL STRENGTH:	>80N
DURABILITY:	>5000 CYCLES

> PHYSICAL

